


8.5 * 11.125



Operating Instructions and Parts Manual

Horizontal/Vertical Bandsaw

Model: HVBS-56M



C US
LR216097

WMH TOOL GROUP
2420 Vantage Drive
Elgin, Illinois 60123
Ph.: 800-274-6848
www.wmhtoolgroup.com

Part No.: M-414458
Revision G 11/03
Copyright © WMH Tool Group

This manual has been prepared for the owner and operators of a JET HVBS-56M. Its purpose, aside from machine operation, is to promote safety through the use of accepted correct operating and maintenance procedures. Completely read the safety and maintenance instructions before operating or servicing the machine. To obtain maximum life and efficiency from your Bandsaw, and to aid in using the machine safely, read this manual thoroughly and follow instructions carefully.

Warranty & Service

The WMH Tool Group warrants every product it sells. If one of our tools needs service or repair, one of our Authorized Repair Stations located throughout the United States can give you quick service.

In most cases, any one of these WMH Tool Group Repair Stations can authorize warranty repair, assist you in obtaining parts, or perform routine maintenance and major repair on your JET, Performax, Wilton, or Powermatic tools.

For the name of an Authorized Repair Station in your area, please call 1-800-274-6848, or visit www.wmhtoolgroup.com

More Information

Remember, the WMH Tool Group is consistently adding new products to the line. For complete, up-to-date product information, check with your local WMH Tool Group distributor, or visit www.wmhtoolgroup.com

WMH Tool Group Warranty

The WMH Tool Group (including Performax, Wilton and Powermatic brands) makes every effort to assure that its products meet high quality and durability standards and warrants to the original retail consumer/purchaser of our products that each product be free from defects in materials and workmanship as follow: 1 YEAR LIMITED WARRANTY ON ALL PRODUCTS UNLESS SPECIFIED OTHERWISE. This Warranty does not apply to defects due directly or indirectly to misuse, abuse, negligence or accidents, normal wear-and-tear, repair or alterations outside our facilities, or to a lack of maintenance.

THE WMH TOOL GROUP LIMITS ALL IMPLIED WARRANTIES TO THE PERIOD SPECIFIED ABOVE, FROM THE DATE THE PRODUCT WAS PURCHASED AT RETAIL. EXCEPT AS STATED HEREIN, ANY IMPLIED WARRANTIES OR MERCHANTABILITY AND FITNESS ARE EXCLUDED. SOME STATES DO NOT ALLOW LIMITATIONS ON HOW LONG THE IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATION MAY NOT APPLY TO YOU. THE WMH TOOL GROUP SHALL IN NO EVENT BE LIABLE FOR DEATH, INJURIES TO PERSONS OR PROPERTY, OR FOR INCIDENTAL, CONTINGENT, SPECIAL, OR CONSEQUENTIAL DAMAGES ARISING FROM THE USE OF OUR PRODUCTS. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU.

To take advantage of this warranty, the product or part must be returned for examination, postage prepaid, to an Authorized Repair Station designated by our office. Proof of purchase date and an explanation of the complaint must accompany the merchandise. If our inspection discloses a defect, we will either repair or replace the product, or refund the purchase price if we cannot readily and quickly provide a repair or replacement, if you are willing to accept a refund. We will return repaired product or replacement at JET'S expense, but if it is determined there is no defect, or that the defect resulted from causes not within the scope of JET'S warranty, then the user must bear the cost of storing and returning the product. This warranty gives you specific legal rights; you may also have other rights which vary from state to

The WMH Tool Group sells through distributors only. Members of the WMH Tool Group reserve the right to effect at any time, without prior notice, those alterations to parts, fittings, and accessory equipment which they may deem necessary for any reason whatsoever.

WARNING

Read and understand the entire instruction manual before operating machine. This machine is designed and intended for use by properly trained and experienced personnel only. If you are not familiar with the proper safe use of bandsaws, do not use this machine until proper training and knowledge has been obtained.

"Warning: For your own safety read instruction manual before operation saw"

- (a) Wear eye protection.
 - (b) Do not remove jammed cut off pieces until blade has stopped.
 - (c) Maintain proper adjustment of blade tension, blade guides, and trust bearing.
 - (d) Adjust upper guide to just clear workpiece.
 - (e) Hold workpiece firmly against table.
1. Keep guards in place and in working order.
 2. Remove adjusting keys and wrenches. Form habit of checking to see that keys and adjusting wrenches are removed from tool before turning it on.
 3. Keep work area clean. Cluttered areas and benches invite accidents.
 4. Don't use in dangerous environment. Don't use power tools in damp or wet locations, or expose them to rain. Keep work area well lighted.
 5. Keep children away. All visitors should be kept safe distance from work area.
 6. Make workshop kid proof with padlocks, master switches, or by removing starter keys.
 7. Don't force tool it will do the job better and safer at the rate for which it was designed.
 8. Use right tool don't force tool or attachment to do a job for which it was not designed.
 9. Use proper extension cord. Make sure your extension cord is in good condition. When using an extension cords, be sure to use one heavy enough to carry the current your product will draw. An undersized cord will cause a drop in voltage resulting in loss of power and overheating. Table shows the correct size to use depending on cord length and nameplate ampere rating. If in double, use the next heavier gage. The smaller the gage number, the heavier the cord.
 10. Wear proper apparel do not wear loose clothing, gloves, neckties, rings, bracelets, or other jewelry which may get caught in moving parts. Nonslip footwear is recommended. Wear protective hair covering to contain long hair.
 11. Always use safety glasses. Also use face or dust mask if cutting operation is dusty. Everyday eyeglasses only have impact resistant lenses, they are NOT safety glasses.
 12. Secure work. Use clamp or a vise to hold work when practical. It is safer than using your hand and it frees both hands to operate tool.
 13. Don't overreach. Keep proper footing and balance at all times.
 14. Maintain tools with care. Keep tools sharp and clean for best and safest performance. Follow instructions for lubricating and changing accessories.
 15. Disconnect tools before servicing; when changing accessories, such as blades, bits, cutters and the like.
 16. Reduce the risk of unintentional starting. Make sure switch is in off position before plugging in.
 17. Use recommended accessories. Consult the owner's manual for recommended accessories. The use of improper accessories may cause risk of injury to person.
 18. Some dust created by power sanding, sawing, grinding, drilling and other construction activities contains chemicals known to cause cancer, birth defects or other reproductive harm. Some examples of these chemicals are:
 - Lead from lead based paint
 - crystalline silica from bricks and cement and other masonry products, and
 - arsenic and chromium from chemically-treated lumber.
 19. Never stand on tool serious injury could occur if the tool is tipped or if the cutting tool is unintentionally contacted.
 20. Check damaged parts. Before further use the tool, a guard or other part that is damaged should be carefully checked to determine that it will operate properly and perform its intended function – check for alignment of moving parts, binding of moving parts, breakage of parts, mounting, and any other conditions that may affect its operation. A guard or other part that is damaged should be properly repaired or replaced.

21. Direction of feed work into a blade or cutter against the direction of rotation of the blade or cutter only.
22. Never leave tool running unattended. Turn power off. Don't leave tool until it comes to a complete stop.

Table
Minimum gage for cord

Ampere Rating		Volts	Total length of cord in feet			
		120V	25 ft.	50ft.	100ft.	150ft.
		240V	50ft.	100ft.	200ft.	300ft.
	Not	AWG				
More	More					
Than	Than					
0	6	18	16	16	14	
6	10	18	16	14	12	
10	12	16	16	14	12	
12	16	14	12	Not Recommended		
Only the applicable parts of the Table need to be included, For instance, a 120-volt product need not include the 240-volt heading						

Grounding Instructions

Caution: This tool must be grounded while in use to protect the operator from electric shock.

In the event of a malfunction or breakdown, grounding provides a path of least resistance for electric current to reduce the risk of electric shock. This tool is equipped with an electric cord having an equipment-grounding conductor and a grounding plug. The plug must be plugged into a matching outlet that is properly installed and grounded in accordance with all local codes and ordinances.

Do not modify the plug provided. If it will not fit the outlet, have the proper outlet installed by a qualified electrician.


Improper connection of the equipment-grounding conductor can result in a risk of electric shock. The conductor, with insulation having an outer surface that is green with or without yellow stripes, is the equipment-grounding conductor. If repair or replacement of the electric cord or plug is necessary, do not connect the equipment-grounding conductor to a live terminal.

Check with a qualified electrician or service personnel if the grounding instructions are not completely understood, or if in doubt as to whether the tool is properly grounded. Use only three wire extension cords that have three-prong grounding plugs and three-pole receptacles that accept the tool's plug.

Repair or replace a damaged or worn cord immediately.

This tool is intended for use on a circuit that has an outlet that looks like the one illustrated in sketch A. The tool has a grounding that looks like the plug illustrated in sketch A. A temporary adapter, which looks like the adapter illustrated in sketches B and C, may be used to connect this plug to a 2-pole receptacle as shown in sketch B if a properly until a properly grounded outlet can be installed by a qualified electrician. (This adapter is not permitted in Canada) The green-colored rigid ear, lug, the like, extending from the adapter must be connected to a permanent ground such as a properly grounded outlet box.

This tool is intended for use on a circuit that has an outlet that looks like the one illustrated in sketch D. The tool has a grounding that looks like the plug illustrated in sketch D. Make sure the tool is connected to an outlet having the same configuration as the plug. No adapter is available or should be used with this tool. If the tool must be reconnected for use on a different type of electric circuit, the reconnection should be made by qualified service personnel; and after reconnection, the tool should comply with all local codes and ordinances.



The conversion from 115V to 230V operation must be done by a qualified electrician.




Chart 1




Chart 2

Specifications:**HVBS-56M**

Stock Number	414458
Horizontal Capacity:	
Round @ 90°	5"
Round @ 45°	3"
Rectangle @ 90°	5" x 6"
Rectangle @ 45°	5" x 3"
Throat Depth	6"
Vertical Work Table Size	9-5/8" x 9-1/2"
Vise Swivels	45°
Blade Size	1/2" x 0.025" x 64-1/2"
Blade Wheel Diameter	7-3/8"
Speeds	80, 120, 200 SFPM
Bed Height	25-1/2"
Floor Space Required	16-1/4" x 42-1/2"
Motor (UL listed)	1/2 HP, 1 Ph, 115/230V, prewired 115V
Net Weight (approx.)	115 lbs.

Table of Contents**Page**

Warranty	2
Warnings	3-4
Ground instructions	5-6
Specifications & Table of Contents	7
Unpacking & Clean-Up	8
Tools Supplied for Assembly	8
Tools Required for Assembly	8
Assembly	8-10
Vertical Cutting Plate Assembly	10-11
Electrical Connections	11
Changing Blade Speed	12
Adjusting Blade Guides	12
Adjusting Blade Tension	12
Changing Blades	13
Adjusting Blade Guide Bearings	13
Adjusting Blade Tracking	14
Adjusting Feed Pressure	14
Adjusting Automatic Shut-Off	15
Adjusting the Vise	15
Breakdown for Bow Assembly	16
Breakdown for Base Assembly	17
Parts List	18-20
Wiring Diagram	20

The specifications in this manual are given as general information and are not binding. JET Equipment & Tools reserves the right to effect, at any time and without prior notice, changes or alterations to parts, fittings, and accessory equipment deemed necessary for any reason whatsoever.

Unpacking and Clean-Up

Note: Read and understand the entire manual before attempting setup or operation.

1. Remove all contents from the shipping carton.
2. Inspect contents for shipping damage and report any damage to your distributor.
3. Wipe bed and vise assembly with clean cloth to remove excess oil used to prevent rust.
4. Do not discard any packing material until saw has been assembled and is running properly.

Tools Supplied for Assembly

1. Wrench 12/14mm
2. 4mm Angle Hex Wrench

Tools Required for Assembly

- #2 Cross Point Screwdriver
- 6-8" Adjustable Wrench or Wrench Set
- Pliers - Regular or Needle Nose
- Ratchet and Sockets will Speed Assembly

Assembly

1. With the help of another person turn the saw over so that it rests on the motor and saw bow, Figure 1. Place it on a piece of cardboard, or a surface that will not damage the saw.
2. Attach a cross brace (A, Fig. 1) to the motor side of the bed using three 5/16"x1" hex cap bolts, six 5/16" flat washers, and secure with three 5/16" hex nuts. **Hint:** Tighten the nut (B, Fig. 1) on the end of the bed first followed by the nuts on the sides.
3. Attach a leg to the cross brace using four 5/16"x3/4" carriage bolts, four 5/16" flat washers and four 5/16" hex nuts. Use a 12mm wrench to tighten. Repeat for other leg.
4. Remove the brace (C, Fig. 1) on the opposite end of the bed and bow using a 10mm wrench.





Fig. 1

5. Attach a cross brace to the opposite end of the bed using three 5/16"x1" hex cap bolts, six 5/16" flat washers, and secure with three 5/16" hex nuts. Tighten the nut on the end of the bed first followed by the nuts on the sides.

6. Attach a leg to the cross brace using four 5/16"x3/4" carriage bolts, four 5/16" flat washers and four 5/16" hex nuts. Use a 12mm wrench to tighten. Repeat for other leg.

7. Attach the adjustable feet (A, Fig. 2) to the legs opposite of the motor, using the provided hardware.

8. Slide the axle (A, Fig. 3) through the legs. Place a large flat washer (B, Fig. 3) on both sides of the wheels and place on the axle. Secure wheels with two split pins (C, Fig. 3).

9. Carefully turn the saw onto its stand and adjust the feet so the bed is level.

10. Put the handle (A, Fig. 4) through holes in the stand legs opposite of the wheel assembly and secure with split pins.




Fig. 2




Fig. 3




Fig. 4

11. Slide pulley cover (A, Fig. 5) around motor shaft and worm gear shaft. Secure with two hex cap screws and washers (B, Fig. 5).
12. Lift motor with one hand while the other hand places V-belt (C, Fig. 5) on both pulleys.
13. Attach the tension bracket (D, Fig. 5) to the saw bow with one 5/16"x3/4" hex head bolt and flat washer (E, Fig. 5).
14. Connect the two tension brackets with one 5/16"x3/4" carriage bolt, one 5/16" flat washers and one 5/16" hex nut (F, Fig. 5).
Hint: Insert the carriage bolt from the inside so the hex nut is easy to access with a wrench.
15. Tension belt by pressing down on the motor while tightening hex nut (F, Fig. 5) until finger pressure on the belt between the two pulleys causes approximately 1/2" deflection. Close pulley cover. Don't over tighten the belt.
16. Insert stop rod (A, Fig. 6) into bed and tighten set screw (B, Fig. 6). Slide stock stop (C, Fig. 6) onto rod and tighten set screw (D, Fig. 6) to hold in place.
17. Slide handwheel (E, Fig. 6) onto shaft and secure by tightening set screw (F, Fig. 6). Make sure set screw seats on flat portion of shaft.




Fig. 5




Fig. 6

Vertical Cutting Plate Assembly

Note: These steps are only necessary when using the bandsaw in the vertical mode.

⚠ WARNING
Disconnect the bandsaw from the power source before making any repairs or adjustments!
Failure to comply may cause serious injury!

1. Disconnect the bandsaw from the power source.
2. Raise the arm to the vertical position and lock in place with lever (A, Fig. 7).
3. Loosen bolt (B, Fig. 7) and insert bracket (C, Fig. 7). Tighten bolt just enough to hold the bracket in place.




Fig. 7

4. Remove two screws (D, Fig. 7) and plate (E, Fig. 7).
5. Guide blade through slot in table (A, Fig. 8) and fasten table with two screws (B, Fig. 8).
6. Fasten support bracket to underside of table using screw (C, Fig. 8) and hex nut.
7. Tighten bolt (B, Fig 7).




Fig. 8

Electrical Connections

WARNING

**All electrical connections must be completed by a qualified electrician.
Failure to comply may cause serious injury!**

The HVBS-56M band saw is rated at 115/230V and comes from the factory prewired 115V.

To switch to 230V operation, follow the wiring diagram found on the inside of the motor junction box. The plug on the end will have to be replaced with a plug that is rated at 230V.

Before hooking up to the power source, be sure the switch is in the off position.

Changing Blade Speed

1. **Disconnect the machine from the power source.**
2. Place saw arm in the horizontal position.
3. Loosen tensioning plate hex nut (A, Fig. 10).
4. Open pulley cover (B, Fig. 10). Lift motor with one hand while placing the belt (C, Fig. 10) on the desired pulley combination.
5. Tension belt by pressing down on the motor while tightening hex nut (A, Fig. 10) until finger pressure on the belt between the two pulleys causes approximately 1/2" deflection. Close pulley cover. Don't over tighten the belt.
6. Close pulley cover and connect to power source.

The general rule for band saw blade speed is the harder the material being cut, the slower the blade speed. Reference Figure 11 for a guide to blade speed for a type of material being cut.

Adjusting Blade Guides

1. **Disconnect machine from the power source.**
2. Loosen knob (A, Fig. 12) and slide blade guide assembly (B, Fig. 12), as close as possible without interference to the material being cut. Tighten knob.
3. Loosen bolt (C, Fig. 12) and slide blade guide assembly (D, Fig. 12), as close as possible without interference to the material being cut. Tighten bolt

Adjusting Blade Tension

1. **Disconnect machine from the power source.**
2. Open blade cover and observe the position of the blade on the wheel. If the blade is not next to the wheel flange, adjust blade tracking following the steps under "Adjusting Blade Tracking".
3. If the blade is next to the wheel flange, loosen the blade guide assembly lock knob and hex head bolt (A & C, Fig. 12) and slide

the blade guide assemblies as far apart as possible. Lock in place.

4. Depress blade. Finger pressure should cause approximately .004" deflection. Turn blade tension knob (B, Fig. 12) until the proper tension is achieved. Re-position guides for cutting material.




Fig. 10

Material	Speed	Motor Pulley	Saw Pulley
Tool, Stainless, or Alloy Steel, Bearing Bronzes	80 FPM	Small	Large
Mild Steel, Hard Brass, or Bronze	120 FPM	Medium	Medium
Soft Brass, Aluminum, or other light materials	200 FPM	Large	Small

Fig. 11




Fig. 12

Changing Blades

1. **Disconnect machine from the power source.**
2. Raise the saw arm to the vertical position and lock in place with lock lever.
3. Open blade cover by removing the small knob found on the topside of the bow.
4. Remove red blade guards by removing two screws.

WARNING

It is essential these two guards be installed after the new blade has been fitted. Failure to comply may cause serious injury!

5. Release tension on the blade by turning tensioning knob (B, Fig. 12), and remove the blade.
6. Place new blade between the blade guide assemblies and around each wheel. Make sure blade teeth are pointing in the proper direction, Figure 13. Tension enough to hold in place.
7. Install red blade guards with two screws.
8. Tension blade fully, see "Adjusting Blade Tension".
9. Place two to three drops of lightweight oil on the blade.
10. Connect machine to the power source.
11. Run saw and make sure blade is tracking properly, see "Adjusting Blade Tracking".

As a general rule, the thinner the material to be cut, the more teeth per inch on the blade. A minimum of three teeth should be in contact with the material at all times during the cut. If the teeth straddle the material, severe damage can result to the material and the blade.

Adjusting Blade Guide Bearings

1. **Disconnect machine from the power source.**
2. Loosen bolt (A, Fig. 14) and adjust assembly so that back roller bearing is approximately .002" - .003" from the back of the blade. Tighten bolt.

3. Loosen nut (B, Fig. 14) and turn nut (C, Fig. 14) to adjust eccentric bearing to a clearance of .001". Tighten nut (B, Fig. 14) to lock.
4. Connect machine to power source.




Fig. 13




Fig. 14

Adjusting Blade Tracking

⚠ WARNING

Blade tracking adjustment requires running the saw with the back cover open! This adjustment must be completed by qualified persons only! Failure to comply may cause serious injury!

Blade tracking has been set at the factory and should not need adjustment. If blade tracking needs to be adjusted:

1. Confirm that blade tension is set properly. To adjust, see section titled "Adjusting Blade Tension".
2. Make sure the saw is in its slowest speed, see "Changing Blade Speeds".
3. Move saw arm to the vertical position and lock in place with the lock lever.
4. Confirm that blade tension is set properly. To adjust, see section titled "Adjusting Blade Tension".
5. Open blade cover by removing the knob found on the top side of the bow.
6. Run saw and observe blade. Blade should run next to but not tightly against wheel flange.
7. Loosen bolts (A, Fig. 15).
8. Turn set screw (B, Fig. 15) while observing blade tracking on wheel. Turn set screw clockwise to track closer to wheel flange. Turn set screw counter-clockwise to track away from the wheel flange. **Hint:** start with $\frac{1}{4}$ turns on the set screw. The tracking is sensitive.
9. Once tracking is set, tighten bolts (A, Fig. 15).

Adjusting Feed Pressure

1. Turn handle (A, Fig. 16) clockwise to decrease cutting pressure and counter-clockwise to increase cutting pressure.

A good indication of proper feed pressure is the color and shape of the cutting chips. If the chips are thin or powdered, increase the feed pressure. If the chips are burned and heavy, decrease the

feed pressure. If they are still burned and heavy, reduce the blade speed. Optimum feed pressure has been set when the chips are curled, silvery, and warm.




Fig. 15




Fig. 16

Adjusting Automatic Shut-Off

The saw should stop after the cut has been completed:

- If the saw completes the cut and continues to run, adjust the stop tip (A, Fig. 17) down.
- If the saw shuts off before the cut is complete, adjust the stop tip (A, Fig. 17) up.
- If the saw stops cutting but continues to run, adjust the stop bolt (B, fig. 17) down.

The saw is properly adjusted when the saw shuts off just after the blade has finished the cut.

Adjusting the Vise

1. To open and close the vise use the handwheel (C, Fig. 17).
2. The vise can be adjusted for square and miter cuts. Loosen the hex cap bolts and adjust the vise for the cut.
3. Adjust the blade guides so they are as close as possible to the material without interfering.
4. There is a scale on the back side of the bed to aid in setting up the vise for 90° cuts or a particular miter. **Hint:** Always check the vise setup with a combination square, against the blade and vise, so that you can verify the vise setting is correct.

Lubrication

Ball bearings on the blade guide assemblies and the blade wheels are permanently sealed and require no lubrication.

Lubricate the vise lead screw as needed with #2 tube grease.

Gear box oil will have to be changed after 90 days of operation. There after, change every six months.

To change the gear box oil:

1. **Disconnect machine from the power source.**

2. Place saw arm in the horizontal position.
3. Remove screws (A, Fig. 18) from the gear box and remove cover plate and gasket.
4. Hold a container under the lower right corner of the gear box with one hand while slowly raising the saw arm with the other. Drain completely.
5. Place arm in the horizontal position. Wipe out remaining oil with a rag.
6. Fill gear box with approximately 1/2 pint of MOBIL SHC 634.
7. Replace gasket and cover. Fasten cover with bolts.




Fig. 17






Fig. 18

Breakdown for Bow Assembly



Breakdown for Base Assembly




Parts List for the HVBS-56M Band saw

Index No.	Part No.	Description	Size	Qty.
1	TS-0051031	Hex Cap Bolt	5/16"x3/4"	4
2	TS-0561011	Hex Nut	1/4"	1
3	TS-0680021	Flat Washer	1/4"	5
4	HVBS56M-04	Stand Leg		4
4-1	HVBS56M-04-1	Cross Brace		2
5	HVBS56M-05	Washer		6
6	HVBS462-006	Cotter Pin	1/8"x1"	4
7	HVBS56M-07	Axle		1
8	TS-0680031	Flat Washer	5/16"	36
9	HVBS56M-09	Wheel		2
10	HVBS56M-010	Washer	1/4"x5/8"	1
11	TS-0051051	Hex Cap Bolt	5/16"x1"	4
11-1	HVBS56M-11-1	Carriage Bolt	5/16"x3/4"	16
11-2	TS-0051051	Hex Cap Bolt	5/16"x1"	6
12	TS-0561021	Hex Nut	5/16"	22
13	HVBS56M-013	Adjustable Foot		2
14	HVBS462-014	Floor Stand Handle		1
15	HVBS462-015	Adjusting Rod		1
16	HVBS462-016	Electric Cord		1
17	HVBS462-017	Pivoting Rod		1
18	HVBS462-018	Support Plate		1
19	HVBS462-019	Stock Stop		1
20	TS-0270021	Socket Set Screw	5/16"x5/16"	4
21	HVBS462-021	Stock Stop Rod		1
22	HVBS462-022	Wire Relief Retainer		2
25	TS-0051031	Hex Cap Bolt	5/16"x3/4"	1
27	HVBS462-027	Wheel Handle		1
28	HVBS462-028	Hand Wheel		1
29	HVBS56M-029	Toggle Switch Assembly		1
29-1	HVBS56M-029-1	Plastic Cover		1
30	HVBS462-030	E-Ring	E10	1
31	HVBS462-031	Screw	5/16"x1"	3
32	HVBS462-032	Lead Screw		1
33	HVBS462-033	Vise Nut		1
34	HVBS462-034	Moveable Vise Plate		1
35	TS-0680041	Flat Washer	3/8"x1"	4
36	TS-0090061	Hex Cap Bolt	3/8"x1-1/4"	1
37	HVBS462-037	Bed		1
38	HVBS462-038	Cross Round Head Screw	3/16"x3/8"	2
39	HVBS462-039	Scale		1
40	HVBS462-040	Electric Cord Clip		1
42	HVBS56M-042	Screw	M4x16	2
43	HVBS462-043	Rubber Ring		1
44	HVBS462-044	Electric Cable		1
45	HVBS462-045	Nut Plate		1
45-1	HVBS56M-045-1	Spring Handle Bracket		1
46	HVBS462-046	Spring Adjusting Screw		1
47	HVBS462-047	Spring		1
48	HVBS462-048	Cross Round Head Screw	3/16"x3/8"	4
49	HVBS462-049	Mitering Vise Plate		1
50	TS-0081031	Hex Cap Bolt	5/16"x3/4"	6
51	TS-0680031	Flat Washer	5/16"	3

Index No.	Part No.	Description	Size	Qty.
52	TS-0081071	Hex Cap Bolt	5/16"x1-1/2"	1
53	TS-0091071	Hex Cap Screw	7/16"x2"	1
54	HVBS56M-054	Pivot Bracket		1
55	HVBS462-055	Vertical Cutting Plate		1
56	HVBS462-056	Stand for Vertical Cutting Plate		1
57	HVBS56M-057	Adjustable Bracket Assembly LH		1
58	HVBS462-058	Knob	1/4"	2
59	HVBS56M-059A	Blade Back Safety Cover		1
60	HVBS462-060	C-Clip	S10	4
61	BB-6000ZZ	Ball Bearing	6000ZZ	6
62	HVBS462-062	Guide Pivot		2
	HVBS462-062A	Center Shaft Assembly (Includes: #60-62)		1
62-1	HVBS462-062-1	Centrifugal Guide Pivot		2
	HVBS462-062-1A	Eccentric Shaft Assembly (Includes: #60,61,62-1)		1
63	HVBS462-063	Bearing Shaft Pin		2
64-1	HVBS462-064-1	Blade Seat Left		1
64-2	HVBS462-064-2	Blade Seat Right		1
65	HVBS56M-065	Adjustable Bracket-Assembly RH		1
66	HVBS462-066	Lock Knob		1
67	TS-0720081	Lock Washer	5/16"	3
68	TS-0813051	Flat Head Machine Screw	1/4"x3/4"	3
69	HVBS462-069	Bearing Guard		1
70	TS-0561031	Hex Nut	3/8"	4
71	HVBS462-071	Blade Wheel Drive		1
72	HVBS462-072	Bearing Cover		2
73	HVBS462-073	Key	5x5x25	2
74	HVBS56M-060	C-Clip	S15	1
75	HVBS462-075	Hex Cap Bolt (w/Washer)	1/4"x1/2"	8
76	HVBS462-076	Switch Cut Off Trip		1
77	HVBS462-077	Idle Blade Wheel		1
78	TS-0680031	Flat Washer	5/16"	2
79	HVBS462-079	Blade Tension Knob	3/8"	1
80	HVBS462-080	Spring		1
81	HVBS56M-081	Saw Bow		1
82	HVBS56M-082	Washer		1
83	TS-0070031	Cap Screw	1/2"x1-1/2"	2
84	HVBS56M-084	Motor Mount Plate		1
84-1	HVBS56M-084-1	Tension Bracket		1
85	HVBS463-085	Motor	1/2 HP, 1Ph	1
	HVBS463-085-01	Capacitor Cover (not shown)		1
	HVBS462-085-02	Capacitor (not shown)		1
86	HVBS462-086	Motor Pulley		1
87	BB-6202ZZ	Ball Bearing	6202ZZ	6
88	HVBS462-088	Bearing Bushing		1
89	OS-15375	Oil Seal		2
90	HVBS462-090	Transmission Wheel Shaft		1
91	HVBS462-091	Worm Gear		1
92	HVBS462-092	Gear Box Gasket		1
93	HVBS462-093	Gear Box Cover		1
94	HVBS462-094	Worm Gear (w/Shaft)		1
95	HVBS462-095	Spring Pin		1
96	HVBS462-096	Bearing Bushing		1
97	TS-0050011	Hex Cap Bolt	1/4"x1/2"	3
98	HVBS56M-098	Clamp		2

Index No.	Part No.	Description	Size	Qty.
99	HVBS462-099	Spacer		1
100	HVBS462-100	Flat Cross Head Screw	5/32"x3/8"	8
101	HVBS462-101	Worm Gear Pulley		1
102	TS-0720081	Lock Washer	5/16"	2
103	HVBS462-103	Blade Tension Sliding Plate		1
104	TS-0270051	Socket Set Screw	5/16"x1/2"	3
105	HVBS462-105	Spring Pin		1
106	HVBS462-106	Sliding Plate Draw Block		1
107	HVBS462-107	Blade Wheel Shaft		1
108	HVBS462-108	Shaft Block		1
109	HVBS462-109	Blade Tension Sliding Guide		2
110	HVBS462-110	Motor Pulley Cover Assembly		1
111	TS-0680031	Flat Washer	5/16"	1
112	VB-A22	V-Belt	A22	1
113	414301	Blade		1
114	TS-0680041	Flat Washer	3/8"	4
115	TS-0561011	Hex Nut	1/4"	1
116	HVBS463-170	Wire Plug		3
117	HVBS463-171	Hex Screw	3/8"x1-1/4"	1
120	HVBS462-120	Bushing		1
122	TS-0561041	Hex Nut	7/16"	1
123	TS-0050031	Cap Screw	1/4"x3/4"	1
124	HVBS463-124	Machine Screw	3/16"x3/4"	2
126	HVBS462-126	Bushing		1
132	HVBS462-132	Blade Guard-Right		1
132-1	HVBS462-132A	Blade Guard-Left		1
156	HVBS462-156	Round Head Screw	3/16"x3/4"	1
157	HVBS462-157	Star Washer	3/16"	3
158	HVBS463-158	Hex Nut	3/16"	2
	HVBS56M-BS	Blade Speed Label (not shown)		1
	HVBS56M-ID	I.D. Label (not shown)		1
	HVBS56M-WL	Warning Label (not shown)		1
	JM-56M	Stripe Decal (not shown)		1

Wiring Diagram





WMH Tool Group
2420 Vantage Drive
Elgin, Illinois 60123
Phone: 800-274-6848
www.wmhtoolgroup.com